

PRODUCT DATASHEET

1. TECHNICAL DATA

ITEM CODE	SIZE	WEIGHT	HEIGHT	LENGTH	DEPTH	CAPACITY
9V3823	1 cup	200 g	13 cm	11,5 cm	7 cm	12cl
9V3824	3 cups	350 g	16,5 cm	14,5 cm	9 cm	22cl
9V3825	6 cups	520 g	20.5 cm	17 cm	10 cm	33cl

MATERIAL	<p><u>Aluminium</u> suitable food contact (Boiler, upper part, disk filter, funnel filter)</p> <p>The chemical composition of aluminium and aluminium alloys used by GAT are conform to the standards UNI EN 601/602 (Aluminium and aluminium alloys suitable food contact)</p>
	<p><u>Plastic</u> material (handle, knob and lid)</p> <p>The plastic materials used are conform to the standards DM 21-3-1973 (legislation concerning materials and articles in contact with foodstuffs)</p>
	<p><u>Silicon</u> material (Gasket)</p> <p>The silicon gasket used are conform to the standards DM 21-3-1973 (legislation concerning materials and articles in contact with foodstuffs)</p>

Documento	Versione	Redatto	Data	
	01	Ufficio tecnico	21/03/2016	

PRODUCT DATASHEET

2. DESCRIPTION OF THE APPLIANCE

The appliance is composed of the following components

Pitcher lid	Material: <u>Polycarbonate</u>
Knob	Material: plastic with chromed decoration. The knob does not get in touch with coffee.
Handle	Ergonomically handle designed for ensure the maximum safety when using the coffee-maker. This type of handle makes it easy to carry and pour coffee. The handle does not get in touch with coffee.
Boiler, lid and upper part	Material: <u>Aluminium</u> suitable food contact.
Disk filter	Material: <u>Aluminium</u> suitable food contact.
Gasket	Silicon Gasket
Safety valve	<p>Opening pressure of safety valve: 2÷3,5 Bar (in according to UNI EN 13248:2004 - Cookware - Coffee makers for domestic use with an independent heat source -. Definition, requirements and test methods)</p> <p>Control parameter of safety valve (in according to UNI EN 2859/1):</p> <ul style="list-style-type: none"> - Type of sampling: attributes control - Sampling plan: Simple sampling - Sample units: safety valve - AQL Level: 0
Funnel filter	<p>Material: <u>Aluminium</u> suitable food contact.</p> <p>Dimensional control: conformity of the distance bottom/funnel in accordance with norm UNI EN 13248;2004 (§4.2.6) “Cookware. Coffee makers for domestic use with an independent heat source. Definitions, requirements and test methods”. Acceptance criterion: minimum distance allowed 2 mm</p>

Documento	Versione	Redatto	Data	
	01	Ufficio tecnico	21/03/2016	